



Sample image

KG212

Type Size: S2

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Bolt terminal/Screw terminal

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107

Rated insulation voltage Ui

Voltage (V)	AC / DC
1000	AC

Rated impulse withstand voltage Uimp

Voltage (kV)	Overtoltage category	Pollution degree	Supply system	Function
8	III	3	Valid for lines with grounded common neutral termination	Switch / Switch disconnecter

Rated uninterrupted current Iu/lth

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	additional requirements
200	50	55	Ambient temperature +50°C during 24 hours with peaks up to +55°C

Conventional enclosed thermal current Ithe

Current (A)	Ambient temperature (°C)	Peak temperature (°C)	Additional requirements	No. of stages (from - to)	Mounting	Mounting size
200	35	40	Ambient temperature +35°C during 24 hours with peaks up to +40°C	--	--	--

Rated operational current Ie

Utilization category	Voltage (V)	Current (A)
AC-20A	1000	200
AC-21A	20 - 690	200
AC-22A	220 - 500	200
AC-22A	660 - 690	125

Rated operational power

Utilization category	Voltage (V)	No. of phases	No. of poles	Power (kW)
AC-3	220 - 240	3	3	37
AC-3	380 - 440	3	3	55
AC-3	500 - 500	3	3	75
AC-3	660 - 690	3	3	40
AC-23A	220 - 240	3	3	37
AC-23A	380 - 440	3	3	75
AC-23A	500 - 500	3	3	90
AC-23A	660 - 690	3	3	45

Max Fuse Rating IEC

Fuse characteristic	No. of Fuses	Current (A)
gG	1	200

UL60947-4-1, UL508

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current

Current (A)	Ambient temperature (°C)	Additional Text
200	0 - 40	--

General Information
Text

- The operating handle and position indicating means to be used with these manual motor controllers should be provided from the manufacturer, or the operating handle and position indicating means to be used should have been previously evaluated in combination with the manual motor controllers.

CSA

Rated insulation voltage Ui

Voltage (V)	AC / DC
600	AC

Rated thermal current			
	Current (A)	Ambient temperature (°C)	Additional Text
	200	0 - 40	--

GENERAL TECHNICAL INFORMATION

Tightening torque of screws		
	tightening torque (Nm)	tightening torque (lb-in)
	16	140

Rated short-time withstand current Icw		
	Time (s)	Current (A)
	1	4000

Size of conductor				
composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
flexible wire	Max.	1	MCM 300	Copper
flexible wire	Max.	1	150mm ²	Copper
Single-core or stranded wire	Max.	1	185mm ²	Copper
Single-core or stranded wire	Max.	1	MCM 350	Copper
flexible wire with sleeve	Max.	1	120mm ²	Copper

Approbations		Marking
Specification		
EAC		
CE marking		
UK Directives		
IEC 60947-3; EN 60947-3; VDE 0660 Teil107		IEC 60947-3 EN 60947-3
UL 60947-4-1; CSA C22.2 No. 60947-4-1		
CSA C.22.2 No.14		

Power loss per pole		Power (W)
		5

Conditions during transport and storing			
	Minimum temperature (°C)	Maximum temperature (°C)	additional requirements
	-40	85	In case of temperatures below -5°C no shock load permissible

General Information	
Text	
- The wiring aid has to be removed before voltage is applied!	
- Do not lubricate or treat contacts.	
- Switches may only be mounted, connected and set into operation by qualified persons according to the accepted rules of technology.	

Operating temperature		
	Min. Temperature [°C]	Max. Temperature [°C]
	-5	55

ring type terminal dimensions

A(mm)	25,00 mm
A(mm)	34,00 mm